



US005408832A

[11] Patent Number: 5,408,832

[45] Date of Patent: Apr. 25, 1995

3,461,678 8/1969 Klipping et al. .... 62/45.1  
3,514,006 5/1970 Molnar ..... 220/14  
4,000,246 12/1976 Waller .  
4,048,361 9/1977 Vahyi .  
4,154,364 5/1979 Hagiwara et al. .  
4,159,359 6/1979 Pelloux-Gervais .  
4,269,323 5/1981 Ito et al. .  
4,444,821 4/1984 Young et al. .  
4,510,758 4/1985 Tench, Jr. .... 62/45.1  
4,529,638 7/1985 Yamamoto et al. .  
4,536,409 8/1985 Farrell et al. .  
4,662,521 5/1987 Moretti .  
4,668,551 5/1987 Kawasaki et al. .  
4,668,555 5/1987 Uekado et al. .  
4,669,632 6/1987 Kawasaki et al. .  
4,681,788 7/1987 Barito et al. .  
4,683,702 8/1987 Via .  
4,702,963 10/1987 Phillips et al. .  
4,726,974 2/1988 Nowobilski et al. .  
5,018,328 5/1991 Cur et al. .  
5,082,335 1/1992 Cur et al. .  
5,091,233 2/1992 Kirby .

#### FOREIGN PATENT DOCUMENTS

1157711 12/1982 U.S.S.R. .... 62/46.3

Primary Examiner—Ronald C. Capossela  
Attorney, Agent, or Firm—Quaintance & Murphy

#### [57] ABSTRACT

Improved process for evacuating the thermally insulating jacket of a dewar having an inner wall and an outer wall, with the inner space between said walls completely or partially filled with an insulating material, containing also a moisture sorbing material and a getter material, in which said moisture sorbing material is a chemical drying agent.

20 Claims, 2 Drawing Sheets

